



AMP3104A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN design
Instantaneous bandwidth
Suitable for all single channel modulation standards
Small form factor & light weight
Built-in protection circuits
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	5.6 - 6.2 GHz	
Power Output @ P1dB GCP	50 Watt Min	CW
Power Gain	47 dB Min	
Power Gain Flatness	2.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	37 dBm/Tone, $\Delta = 1$ MHz
Harmonics	-20 dBc Typ	At rated Pout
Non-Harmonics Spurious	-60 dBc Max	
Operating Voltage	32 VDC $\pm$ Nom	
Current Consumption	18 Amp Max	At rated Pout
Max Input Power Protection	+8 dBm	10 Sec. without damage
Load VSWR Protection	$\infty : 1$	1 Minute @ rated output

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	230 x 106 x 27 mm 250 x 106 x 27 mm	Excluding Connectors Option 101 and 102
Weight	1.3 Kg.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

AMP3104A SOLID STATE HIGH POWER AMPLIFIER

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	OPTION 103 - Variable Voltage Attenuator
3	CURRENT SENSOR	$I_D @ 20\text{mV}/100\text{mA Typ}$
4	TEMP SENSOR	$V_T @ 10\text{mV}/^\circ\text{C} + 500\text{mV Typ}$
5	SHUTDOWN	TTL - Optional $5\mu\text{s}$ switching speed
6, 7	VDD	28VDC
8, 9	GND	Ground

OUTLINE DRAWING

