

# AMP2107DB-2 SOLID STATE HIGH POWER AMPLIFIER

#### FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications Small form factor, rack mounted Dual-Band system Class A/AB Linear design High Power Advanced technology devices Instantaneous ultra-wide bandwidth Built-in protection circuits, with extensive monitoring Local LCD & remote flexible interfaces

High efficiency, with unprecedented reliability and ruggedness

#### ELECTRICAL SPECIFICATIONS: 50Ω, 25°C



Parameter	Specification		Notes
Band	Band A	Band B	
Operating Frequency Range by Band	0.7 - 6.0 GHz <sup>3</sup>	6.0 - 18.0 GHz	Band A Spillover down to 500MHz <sup>3</sup>
Power Output CW Band A / Band B	15 Watt Min		CW or Pulse
Power Gain	42 dB Min		OdBm or less for Rated Power
Power Gain Flatness	4.0 dB p-p Max	5.0 dB p-p Max	Constant input power
Gain Adjustment Range	>20 dB Typ		Local or remote capable
Input Return Loss	-10 dB Max		
2-Tone Intermodulation (IMD) Band A / Band B	-30 dBc Typ		32dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ		At rated Pout
Spurious	-60 dBc Max		Non-harmonics
Operating Voltage	100 - 240 VAC		47-63 Hz
Power Consumption	300 Watt Max		At rated Pout
Input Power Protection	+10 dBm Max <sup>1</sup>		
Load VSWR Protection	4 : 1: Max <sup>2</sup>		Foldback @ preset limit
Sample Port (optional)	-40 dB		N-Female

1 Units with optional digital monitor and control, for basic units <10 Sec without damage

2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

3 Band A spillover frequency range is functional down to 500MHz with non-specified gain/power variation.

### **ENVIRONMENTAL CHARACTERISTICS**

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport <sup>3</sup>	

3 MIL Spec available for quotation

e

#### **MECHANICAL SPECIFICATIONS**

Parameter	Specification	Notes	
Dimensions W x H x D	430 x 133 x 560 mm	3U, excluding handles	
Weight	17 kg.		
RF Connectors, Input / Output / Sample	N-Female	Front or rear panel	
Interface Connector	9-Pin D-Sub	Rear panel	
AC Power	IEC 60320-C14	Or equivalent	
Cooling	Built in Fan Cooling	Variable speed	
<b>OPTIONAL:</b> Digital Monitor & Control (DMC <sup>4</sup> )	Ethernet RJ-45 TCP/IP, RS422/485, USB		
FWD, REV, VSWR, GAIN, ALC, V & I, TEMP,	Optional GPIB Interface	IEEE rear panel	
Optional Safety Interlock (INT)	Open=STBY/Short=RFON	BNC-F rear panel	

4 Option DMC, LCD controller option may reduce output power by up to -0.5dB



# AMP2107DB-2 SOLID STATE HIGH POWER AMPLIFIER

### **AVAILABLE SPECIAL OPTIONS**

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-40dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	14-points standard <sup>5</sup>

5 Consult with factory if additional points would be required

OUTLINE DRAWING SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER



