


AMP4032C-1 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Rack mounted system
Solid-State class Linear design
Instantaneous wide bandwidth
Designed for EMI/RFI, lab, and general communication applications
Suitable for all single channel modulation standards
Local LCD & remote flexible interfaces
High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	17.0 - 22.0 GHz	
Power Output CW	25 Watt Min	
Power Output @ P1dB	20 Watt Min	
Power Gain	44 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	34dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	350 Watt Max	
Input Power Protection	+3 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	483 x 178 x 560 mm	4U - Excluding handles
Weight	23 kg.	
RF Connectors In/Out	2.9 mm K-female	Optional WR51 Output
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	

e

AMP4032C-1 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

