

AMP2070D-LC SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications Small form factor, rack mounted system
Instantaneous ultra-wide bandwidth
Class A/AB Linear design
High power advanced technology devices
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 6.0 GHz	Hotes
Power Output @ Psat	200 Watt Min	CW or Pulse
Power Output @ P1dB	150 Watt Typ	
Power Gain	53 dB Min	OdBm or less for rated Pout
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	Local or remote capable
Input Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	43dBm/Tone, Δ = 1MHz
Harmonics 2 nd / 3 rd	-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	47 - 63 Hz
Power Consumption	1750 Watt Max	At rated output
Input Power Protection	+10 dBm Max ¹	
Load VSWR Protection	4 : 1: Max ²	Foldback @ preset limit
Sample Port (optional)	-50 dB	N-Female

¹ Units with optional digital monitor and control, for basic units <10 Sec without damage

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

³ MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	482 x 221 x 635 mm	5U, excluding connectors
Weight	43 Kg.	
RF Conn. In / Out / Sample (optional)	N-Female	Front or rear panel
Interface Connector	9-Pin D-Sub	Rear panel
AC Power	IEC 60320-C14	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	
OPTIONAL: Digital Monitor & Control (DMC)	Ethernet RJ-45 TCP/IP, RS422/485, USB	
FWD, REV, VSWR, GAIN, ALC, V & I, TEMP,	Optional GPIB Interface	IEEE rear panel
Optional Safety Interlock (INT)	Open=STBY/Short=RFON	BNC-F rear panel

² Units with optional digital monitor and control, for basic units <1 minute at rated Pout



AMP2070D-LC SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-50dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-50dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	11-points standard ⁴

⁴ Consult the factory if additional points are required.

OUTLINE DRAWING

SHOWN WITH LCD DIGITAL CONTROLLER



