

AMP2073BDB-1LC SOLID-STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications Small form factor, rack mounted Dual-Band system
Class A/AB Linear design
High power advanced technology devices
Instantaneous ultra-wide bandwidth
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency, with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification		Notes
Band	Band A	Band B	Band switching @ 15 mS Max
Operating Frequency Range by Band	1.0 - 6.0 GHz	6.0 - 8.0 GHz	CW or Pulse
Power Output @ Psat	200 Watt Min	120 Watt Min	150W Typ 6.0-8.0 GHz
Power Gain	53 dB Min		OdBm or less for rated Pout
Power Gain Flatness	4.0 dB p-p Max		Constant input power
Gain Adjustment Range	20 dB Min		Local or remote capable
Input Return Loss	-10 dB	Max	
2-Tone Intermodulation (IMD)	-30 dB	с Тур	43dBm/Tone, Δ = 1MHz
Harmonics	-20 dB	с Тур	At rated Pout
Spurious	-60 dB	с Мах	Non-harmonics
Operating Voltage	100 - 240 VAC		47 - 63Hz
Power Consumption	2000 Watt Max		At rated output
Input Power Protection	+10 dBr	n Max¹	
Load VSWR Protection	4 : 1: Max ²		Foldback @ preset limit
Sample Port (optional)	-50	dB	N-Female

¹ Units with optional digital monitor and control, for basic units <10 Sec without damage

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

³ MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	421 x 310 x 700 mm	7U, excluding connectors
Weight	40 Kg. Max	
RF Conn. In / Out / Sample (optional)	N-Female	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent, rear panel
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	
OPTIONAL: Digital Monitor & Control (DMC ⁴)	Ethernet RJ-45 TCP/IP, RS422/485, USB	
FWD, REV, VSWR, GAIN, ALC, V & I, TEMP,	Optional GPIB Interface	IEEE rear panel
Optional Safety Interlock (INT)	Open=STBY/Short=RFON	BNC-F rear panel

⁴ Controller will reduce output power by up to typically 0.5dB.

² Units with optional digital monitor and control, for basic units <1 minute at rated Pout



AMP2073BDB-1LC SOLID-STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-50dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-40dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring	Offset correction entry for +/- 0.2dB accuracy	11-points standard ⁵
(with purchase of Option DMC)		

⁵ Consult the factory if additional points are required.

OUTLINE DRAWING

SHOWN WITH LCD DIGITAL CONTROLLER

