

AMP4059P-6KW

SOLID-STATE HIGH-POWER PULSE AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, HIRF/Pulse applications
 Small form factor rack-mounted system
 Class AB linear advanced technology design
 Linear L-Band high power peak pulse applications
 Built-in protection circuits with extensive monitoring
 Local LCD & remote flexible interfaces
 High efficiency with unprecedented reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50 Ω , 25°C

Parameter	Specification			Notes	
Operating Frequency Range	1.5 - 2.0 GHz				
Output Power @ Pulse	6.0 KW Min			Peak Pulse	
Pulse Characteristics	Width	Duty	PRF	Rise/Fall	Droop
	up to 50 μ S	4 % Max	up to 100 KHz	<50 nS Typ	<1 dB
Power Gain	68 dB Min			0dBm or less for rated Pout	
Power Gain Flatness	3.0 dB p-p Max			Constant input power	
Gain Adjustment Range	20 dB Min			Local or remote capable	
Input Return Loss	-10 dB Max				
Output Power On/Off Ratio	-80 dB Min			TTL Gate Control	
Harmonics	-20 dBc Max			At rated output, 4%, 50 μ S	
Spurious	-60 dBc Max			Non-harmonics	
Operating Voltage	100 - 240 VAC			47 - 63Hz	
Power Consumption	2000 Watt Max / <1 KW Typ			At rated Pout	
Input Power Protection	+5 dBm Max ¹				
Load VSWR Protection	4 : 1: Max ²			Foldback @ preset limit	
Sample Port (optional)	-60 dB			N-Female	

1 Units with optional digital monitor and control, for basic units <10 Sec without damage

2 Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport ³	

3 MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	482 x 178 x 730 mm	4U, excluding handles
Weight	34 Kg. Nom	
RF Conn. Input/Output /Sample (optional)	Type N-F / Type 716-F / Type N-F	Front or rear panel
Gate Control	BNC Female	Front panel
AC Power Connector	IEC 60320-C14	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control (DMC) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

e


AMP4059P-6KW SOLID-STATE HIGH-POWER PULSE AMPLIFIER

AVAILABLE SPECIAL OPTIONS


Parameter	Specification	Notes
Option FRS: Forward RF Sample	-60dB, Type N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-50dB, Type N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With purchase of Option DMC)	Offset correction entry for +/- 0.2dB accuracy	6-points standard ⁴

⁴ Consult the factory if additional points are required.

OUTLINE DRAWING SHOWN WITH LCD DIGITAL CONTROLLER



CONTROLLER - PRIMARY (MAIN) SCREENS

	a - Model: Amplifier model number b - STANDBY/ONLINE: Display STANDBY/ONLINE status c - CLEAR/FALUT: Display CLEAR/FAULT status d - STANDBY/ONLINE: Display STANDBY/ONLINE control e -STATUS: Displays fault & alarm monitors f - ALC: ALC menu button g - ETC: Screen selection button h - FWD POWER: Display FWD POWER value i - RFL POWER: Display RFL POWER value j - VSWR: Display VSWR value k - dBm/Watt: Display dBm/Watt selection & status l - dBm/Watt: Display dBm/Watt selection & status m - Volt_Current: Voltage & current monitor selection n - Duty_Temp: Pulse-Duty & temperature monitor selection o - Display status of the selected TABLE menu window
	a - Model: Amplifier model number b - STANDBY/ONLINE: Display STANDBY/ONLINE status c - CLEAR/FALUT: Display CLEAR/FAULT status d - STANDBY/ONLINE: Display STANDBY/ONLINE control e -STATUS: Displays fault & alarm monitors f - ALC: ALC menu button g - ETC: Screen selection button h - FWD POWER: Display FWD POWER value i - RFL POWER: Display RFL POWER value j - VSWR: Display VSWR value k - dBm/Watt: Display dBm/Watt selection & status l - dBm/Watt: Display dBm/Watt selection & status m - Display status of the fault & alarm status
	a - Model: Amplifier model number b - STANDBY/ONLINE: Display STANDBY/ONLINE status c - CLEAR/FALUT: Display CLEAR/FAULT status d - STANDBY/ONLINE: Display STANDBY/ONLINE control e -STATUS: Displays fault & alarm monitors f - ALC: ALC menu button g - ETC: Screen selection button h - FWD POWER: Display FWD POWER value i - RFL POWER: Display RFL POWER value j - VSWR: Display VSWR value k - dBm/Watt: Display dBm/Watt selection & status l - dBm/Watt: Display dBm/Watt selection & status m - Volt_Current: Voltage & current monitor selection n - Duty_Temp: Pulse-Duty & temperature monitor selection o - Display status of the selected TABLE menu window