EXODUS ADVANCED COMMUNICATIONS

AMP20043
SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Designed for EMI/RFI, lab, CW/Pulse and all communication applications
Small form factor, rack mounted system
Suitable for all single channel modulations standards
Class A/AB linear, high power advanced technology devices
Instantaneous ultra-wide bandwidth
Built-in protection circuits, with extensive monitoring
Local LCD & remote flexible interfaces
High efficiency with unprecedented reliability and ruggedness
LEGACY PN: AMP2030-LC



ELECTRICAL SPECIFICATIONS : 25°C, 50Ω

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 6.0 GHz	
Power Output @ Psat	300 Watt Min	CW or Pulse
Power Output @ P1dB	180 Watt Min	
Power Gain	55 dB Min	0dBm or less for rated Pout
Power Gain Flatness	4 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	Local or remote
Input Return Loss	-10 dB Max	
2-Tone Intermodulation (IMD)	-30 dBc Typ	43dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	At rated output
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	200 - 240 VAC	50 - 60Hz
Power Consumption	3.5 KW Max / 3 KW Typ	At rated output
Input Power Protection	+8 dBm Max[1]	
Load VSWR Protection	4 : 1: Max[2]	Foldback @ preset limit
Sample Port (optional)	-50 dB	N-Female

[1] Units with optional digital monitor and control, for basic units <10 Sec without damage
[2] Units with optional digital monitor and control, for basic units <1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	up to 95 %	Non-condensing
Altitude	3000 meters	
Shock & Vibration	Normal transport[3]	

[3] MIL Spec available for quotation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	421 x 220 x 750 mm	5U, excluding handles
Weight	53 Kg. Max	
RF Connectors In/Out/Sample (optional)	Type-N Female	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling: Built in Quiet-Cool	Close circuit Air-liquid cooling	
OPTIONAL: Digital Monitor & Control (DMC[4]) FWD, REV, VSWR, GAIN, ALC, V & I, TEMP, Optional Safety Interlock (INT)	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface Open=STBY/Short=RFON	IEEE rear panel BNC-F rear panel

[4] Option DMC - LCD Controller option may reduce output power by 0.5 dB typical. Please consult the factory for more information.

AMP20043
SOLID STATE HIGH POWER AMPLIFIER

AVAILABLE SPECIAL OPTIONS

Parameter	Specification	Notes
Option FRS: Forward RF Sample	-50dB, Type SMA or N-Female	Front or rear panel
Option RRS: Reflected RF Sample	-50dB, Type SMA or N-Female	Front or rear panel
Option GPIB: GPIB remote control	GPIB IEEE-488 Remote capability	
Included CPM: Calibrated Power Monitoring (With Option DMC Purchase)	Offset correction entry for +/- 0.2dB accuracy	11-points standard[5]

[5] Consult with factory if additional points would be required

OUTLINE DRAWING
SHOWN WITH OPTIONAL LCD DIGITAL CONTROLLER

